## LIST OF THE CLAIMS

Please amend Claims 1, 12, 17, 25, 30 and 33 as follows:

1. (Currently Amended) A plug-in to a host, the plug-in providing one or more special capabilities to the host, the plug-in comprising:

core means for conducting typical operation of the plug-in by which the one or more special capabilities are carried out; and

interface means for interfacing between the core means and a calling entity with respect to operational status of the plug-in, wherein the operational status is provided to a second plug-in that requested the operational status from the plug-in.

2. (Original) The plug-in of claim 1, wherein:

the interface means is a first interface means; and

the plug-in further comprises

second interface means for interfacing between the core means and the host with respect to the typical operation.

3. (Original) The plug-in of claim 1, wherein:

the host tends one or more storage devices and represents a part of a storage area network (SAN); and

the calling entity represents a storage manager of the SAN.

4. (Original) The plug-in of claim 1, wherein, relative to a client-server architecture, the following relationships apply:

the calling entity represents a client relative to the plug-in; and the plug-in represents a server relative to the calling entity.

5. (Original) The plug-in of claim 4, wherein the client-server architecture is the JCore architecture such that the calling entity is a JCore client plug-in and the plug-in is a JCore server plug-in.

100204679-1 Serial No.: 10/667,469 Examiner: Mesfin, Yemane 2 Group Art Unit: 2144

- 6. (Original) The plug-in of claim 1, further comprising: butler means for gathering operational status information (Op\_Stat\_Info) representing the operational status of the plug-in.
- 7. (Original) The plug-in of claim 6, wherein the butler means is operable for performing the gathering of the Op\_Stat\_Info in an on-going manner while the plug-in is plugged-into the host.
- 8. (Original) The plug-in of claim 7, wherein the butler means is further operable to

cause one or more pieces of the Op\_Stat\_Info to be stored upon the one or more pieces being gathered initially, respectively; and

update the one or more pieces, respectively, as is appropriate relative to the ongoing manner by which the butler means gathers the Op\_Stat\_Info.

9. (Original) The plug-in of claim 8, further comprising: status data object (DO) means for storing the Op\_Stat\_Info; wherein

the butler means is further operable for causing the Op\_Stat\_Info to be stored via the status DO means,

the status DO means is accessible by the calling entity via the interface means.

10. (Original) The plug-in of claim 6, wherein the butler means is operable for initiating the gathering of Op\_Stat\_Info in response to receiving a request from the calling entity, and

for performing the gathering, once initiated, of the Op\_Stat\_Info in an ad hoc manner.

11. (Original) The plug-in of claim 10, further comprising:

status data object (DO) means for storing the Op\_Stat\_Info; wherein the butler means is further operable for

causing the Op\_Stat\_Info to be stored via the status DO means, and passing, upon completion of the gathering, the status DO to the calling entity.

12. (Original) A first plug-in to a host, the first plug-in providing one or more special capabilities to a host, the first plug-in comprising:

core means for conducting typical operation of the first plug-in by which the one or more special capabilities are carried out; and

interface means for interfacing between the core means and one or more second plug-ins loaded on one or more external, relative to the host, entities, respectively, regarding respective operation status of the one or more second plug-ins.

13. (Original) The first plug-in of claim 12, wherein:

the interface means is a first interface means; and

the first plug-in further comprises

second interface means for interfacing between the core means and the host with respect to the typical operation.

14. (Original) The first plug-in of claim 12, wherein:

the host is a first host;

the one or more external entities are one or more second hosts that tend one or more storage units, respectively;

the first host and the one or more second hosts represent a part of a storage area network (SAN); and

the host represents a storage manager of the SAN.

15. (Original) The first plug-in of claim 14, wherein, relative to a client-server architecture, the following relationships apply:

the first plug-in represents a client relative to the second plug-in; and

100204679-1 Serial No.: 10/667,469 Examiner: Mesfin, Yemane 4 Group Art Unit: 2144 the second plug-in represents a server relative to the first plug-in.

- 16. (Original) The first plug-in of claim 15, wherein the client-server architecture is the JCore architecture such that the first plug-in is a JCore client plug-in and the second plug-in is a JCore server plug-in.
- 17. (Currently Amended) A method of operating a plug-in to a host, the plug-in providing one or more special capabilities to the host, the method comprising:

interfacing to make available, from the plug-in to an external calling entity relative to the host, operational status information (Op\_Stat\_Info) regarding the plug-in, wherein the operational status is provided to a second plug-in that requested the operational status from the plug-in.

18. (Original) The method of claim 17, further comprising:

exchanging typical information between the plug-in and the host, the exchange of the typical information being a part of typical operation of the plug-in by which the one or more special capabilities are carried out.

19. (Original) The method of claim 17, wherein:

the host tends one or more storage devices and represents a part of a storage area network (SAN); and

the Op Stat Info is made available to a storage manager of the SAN.

- 20. (Original) The method of claim 17, further comprising: gathering the Op\_Stat\_Info in an on-going manner while the plug-in is plugged into the host.
- 21. (Original) The method of claim 20, further comprising: storing one or more pieces of the Op\_Stat\_Info upon initially gathering the one or more pieces, respectively; and

100204679-1 Serial No.: 10/667,469 Examiner: Mesfin, Yemane 5 Group Art Unit: 2144 updating the one or more pieces, respectively, as is appropriate relative to the on-going manner of the gathering step.

- 22. (Original) The method of claim 21, further comprising: using a status data object (DO) to store the Op\_Stat\_Info; and making the status DO accessible by the calling entity.
- 23. (Original) The method of claim 20, further comprising: receiving a request from the calling entity for the Op\_Stat\_Info; initiating the gathering step in response to receiving the request; and performing the gathering step, once initiated, in an ad hoc manner.
- 24. (Original) The method of claim 23, further comprising: using a status data object (DO) to store the Op\_Stat\_Info; and passing, upon completing the gathering step, the status DO to the calling entity.
- 25. (Original) A machine-readable medium including instructions execution of which by a host produces a first plug-in, the first plug-in providing one or more special capabilities to the host, the machine-readable instructions comprising:

a core code segment for conducting typical operation of the first plug-in by which the one or more special capabilities are carried out; and

an interface code segment for interfacing between the core code segment and one or more second plug-ins loaded on one or more external, relative to the host, entities, respectively, regarding respective operational status of the one or more second plug-ins.

26. (Original) The machine-readable instructions of claim 25, wherein: the interface code segment is a first interface code segment; and the machine-readable instructions further comprise

a second interface code segment for interfacing between the core code segment and the host with respect to the typical operation.

100204679-1 Serial No.: 10/667,469 Examiner: Mesfin, Yemane 6 Group Art Unit: 2144 27. (Original) The machine-readable instructions of claim 25, wherein: the host is a first host; and

the one or more external entities are one or more second hosts that tend one or more storage units, respectively;

the first host and the one or more second hosts represent a part of a storage area network (SAN); and

the first host represents a storage manager of the SAN.

28. (Original) The machine-readable instructions of claim 25, wherein, relative to a client-server architecture, the following relationships apply:

the first plug-in represents a client relative to the second plug-in; and the second plug-in represents a server relative to the first plug-in.

- 29. (Original) The machine-readable instructions of claim 28, wherein the client-server architecture is the JCore architecture such that the first plug-in is a JCore client plug-in and the second plug-in is a JCore server plug in.
- 30. (Original) A method of operating a first plug-in to a host, the plug-in providing one or more special capabilities to a first host, the method comprising: obtaining operational status information (Op\_Stat\_Info) from one or more second plug-ins loaded on one or more external, relative to the host, entities, respectively.
- 31. (Original) The method of claim 30, further comprising; exchanging typical information between the first plug-in and the host, the exchange of the typical information being a part of typical operation of the plug-in by which the one or more special capabilities are carried out.
  - 32. (Original) The method of claim 30, wherein: the host is a first host; and

the one or more external entities are one or more second hosts that tend one or more storage units, respectively;

the first host and the one or more second hosts represent a part of a storage area network (SAN); and

the first host represents a storage manager of the SAN.

33. (Currently Amended) A machine-readable medium including instructions execution of which by a host produces a plug-in, the plug-in providing one or more special capabilities to the host, the machine readable instructions comprising:

a core code segment execution of which causes the one or more special capabilities to be carried out during typical operation of the plug-in; and

a status interface code segment for interfacing between the core and a calling entity and by which operational status of the plug-in is made available to the calling entity, wherein the operational status is provided to a second plug-in that requested the operational status from the plug-in.

34. (Original) The machine-readable instructions of claim 33, further comprising:

a central interface code segment for interfacing between the core portion and the host and by which typical information is exchanged between the plug-in and the host, the exchange of the typical information being a part of the typical operation.

35. (Original) The machine-readable instructions of claim 33, wherein: the host tends one or more storage devices and represents a part of a storage area network (SAN); and

the calling entity represents a storage manager of the SAN.

36. (Original) The machine-readable instructions of claim 33, wherein the plug-in, the host and the calling entity are configured according to the JCore architecture such that the client entity represents a client relative to the plug-in and the plug-in represents a server relative to the calling entity.

100204679-1 Serial No.: 10/667,469 Examiner: Mesfin, Yemane 8 Group Art Unit: 2144